



Published on *CD-adapco* (<http://www.cd-adapco.com>)

[Home](#) > Fast Reactor Subassembly Design Modifications for Increasing Electricity Generation Efficiency

---

## Fast Reactor Subassembly Design Modifications for Increasing Electricity Generation Efficiency



Fast reactors are being considered as one element of future nuclear power systems to enable continued use and growth of nuclear power by limiting high-level waste generation. However, their higher cost relative to existing nuclear reactor designs, even with their higher thermal efficiency, results in higher electricity costs making them economically less attractive to nuclear utilities. In an effort to increase thermal efficiency, fuel subassembly design changes are being investigated using computational fluid dynamics simulations. The goal of this study is to evaluate the effects that subassembly hexcan design changes can have on subassembly coolant flow, temperature distribution and hot channel factors. Simulations have been performed for a 19-pin subassembly geometry using typical fuel pin diameters and wire wrap spacers. The results have shown that it should be possible to raise the average coolant outlet temperature without increasing peak temperatures within the subassembly, allowing for higher thermal efficiency.

### **Author Company:**

INL

### **Author Name:**

R. Wigeland

K. D. Hamman

### **Industries:**

### **Products:**

### **Conference:**

CD-adapco is the world's largest independent CFD focused provider of engineering simulation software, support and services. We have over 30 years of experience in delivering industrial strength engineering simulation.

---

**Source URL:** <http://www.cd-adapco.com/presentation/fast-reactor-subassembly-design-modifications-increasing-electricity-generation>

### **Links:**

[1] <http://www.cd-adapco.com/sites/default/files/Presentation/Nuclear%20Fast%20Reactor%20subassembly%20design.pdf>